

# CR LED JADE LANTERN P852 POST TOP



Number of LEDs	12
Power Consumption	26W
Correlated Colour Temperature	Neutral white, 4000K
Glare Rating	G3
Colour Rendering Index	> 70
Optical Cover	PMMA Lenses
Luminaire Luminous Flux	2939 lm
Luminaire Efficacy	Up to 113 lm/W
Electrical Class	I
Control System Input	1-10V and DALI
Lumen Maintenance Output	L80 > 100,000 hours ( 1000mA, Ta = 15°C ) L90 > 100,000 hours ( 750mA, Ta = 15°C )
Driver Current	650mA
Surge Protection	ANSI C62.41.2 high exposure 10kV, 10kA level
Dimming Control	On Request
Lighting Regulation	NEMA Socket
Operating Temperature	-40°C to +25°C ( 1000mA )
-40°C to +40°C ( 350mA )	
Installation Height	4 - 6m
Installation	Ø 60-76 mm •PT Spigot
Post Top Mounting	-10°, -5°, 0°, 5°, 10°
Material	Marine grade LM6 Aluminium (Housing)
Finish	Natural aluminium
Ingress Protection	IP66
Wind Area (SCx)	0.035m <sup>2</sup>
Weight (Total)	4.5kg

**C&R Outdoor Lighting Ltd**

[www.crlighting.co.uk](http://www.crlighting.co.uk)

## CR JADE LED LANTERN SIZES

